


# NEW MAR-M Machinefoot

This product adds a new functionality to the family of levelling feet. It turns fast a simple static solution into a mobile one giving the advantage of being able to move a structure or machine in environments where mechanical means like forklifts or loading pallets are not allowed or are physically not possible.

By using a simple Allen key you will be able to convert a static levelling foot, supplemented by an NBR pad, into a mobile support capable of moving light or medium weight equipments even in a small area where installation might be a problem.

## Assets:

- Flexibility (1 product satisfies 2 needs)
- Speed of action
- Time saving
- Less manpower to move the structure around
- Attractive design



Type		M Gxh
centered wheel	non centered wheel	
01FR1	01FR2	M16x50
02FR1	02FR2	M16x100
03FR1	03FR2	M20x75
04FR1	04FR2	M20x125
05FR1	05FR2	M24x75
06FR1	06FR2	M24x125

With galvanized steel bolt  
 Static load 2.500 Kg  
 Dynamic load on PA wheel 200 Kg  
 Wrench hex 10 for pulling out the wheel  
 Ø 100 PA foot + black NBR

Type		plate
centered wheel	non centered wheel	
020.PF R1	020PF R2	80 x 80

With top square fixing plate in Steel  
 Static load 2.500kg  
 Dynamic load on PA wheel 200kg  
 Top square fixing plate 80 x 80 mm  
 Holes 4 x 8,5 mm  
 Wheel switch in/out 12,5 mm  
 Ø 100 PA foot + NBR rubber



Non-centered-wheel



Centered wheel

